

CRITICAL DESIGN INFORMATION
START EVERY DESIGN BY FINDING "Lnom"


IF "Lnom" IS NOT GIVEN ON THE CUSTOMER DRAWING, USE EITHER THE MAXIMUM LENGTH (Mmax) OR MINIMUM FULL THREAD LENGTH (Lf) FROM THE CUSTOMER DRAWING TO CALCULATE IT USING ONE OF THE FOLLOWING EQUATIONS

PREFERRED: $L_{nom} = M_{max} - Z_4 - .01$
SECONDARY: $L_{nom} = L_f + U + .01$


Lnom MUST BE ON EVERY PART DRAWING
DO NOT CHANGE ANY DIMENSION GIVEN WITHOUT CONSULTING MATHREAD

INSPECTION INFORMATION:

- Lnom ON ROLLED PART IS MEASURED TO THE POINT ON THE LEAD THREAD WHERE IT FIRST REACHES A HEIGHT OF 'W' (0.2xPITCH) WHEN MEASURED FROM THE ROOT OF THE THREAD. (see sketch above)
- MATpoint SHALL HAVE A MINIMUM OF 1.0 COMPLETE TURN OF RADIUSED THREAD. THREAD MUST BE FULLY FORMED, WITH NO UNDER FILL (FLATS, FISSURES) AT PEAK OF THREAD. WHEN VIEWED IN THE DESIGNATED INSPECTION POSITION, THREE COMPLETE RADIUSED THREAD PROFILES MUST BE VISIBLE.
- APPROPRIATE "GO" GAGE MUST COMPLETELY PASS OVER MATpoint SECTION OF THREAD WITH MINIMAL DRAG BEFORE PLATING. GAGE MUST HAVE MINOR DIAMETER VERIFIED TO ANSI/ASME B1.2-1983 BEFORE USE.
- "Z3" MUST BE MEASURED TO TANGENT POINT OF 'R', USING MATHread APPROVED RADIUS CHART FROM POINT "W" TO TANGENT



FINISHED PART DIMENSIONS Z5, Z3, Dx, & U MUST NOT BE USED TO DESIGN THE BLANK!



COARSE THREAD

FINE THREAD

THREAD SIZE & PITCH	R +.000 -.005	Dy MAX	W +.0004 -.0004	Dx	Z ₃ MIN	Z ₄ MAX	U REF
1/4-20		.160	.0100	.193 .189	.062	.110	.113
5/16-18		.210	.0111	.249 .245	.089	.160	.125
3/8-16		.255	.0125	.305 .301	.127	.195	.141
7/16-14		.300	.0143	.356 .352	.152	.240	.161
1/2-13		.350	.0154	.413 .409	.182	.275	.173
9/16-12		.395	.0167	.468 .464	.212	.310	.188
5/8-11		.440	.0182	.523 .519	.252	.360	.205
DIMENSIONS ARE IN INCHES (in)							
1/4-28	.115	.174	.0071	.208 .204	.062	.123	.080
5/16-24	.145	.217	.0083	.263 .259	.087	.162	.094
3/8-24	.175	.272	.0083	.326 .322	.127	.212	.094
7/16-20	.195	.325	.0100	.379 .375	.152	.241	.113
1/2-20	.235	.365	.0100	.442 .438	.182	.295	.113
9/16-18	.255	.414	.0111	.498 .494	.212	.313	.125
5/8-18	.295	.474	.0111	.561 .557	.252	.381	.125

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN IS THE PROPERTY OF MATHREAD INC. ANY USE, DISCLOSURE OR COPYING IS PROHIBITED EXCEPT WITH THE WRITTEN AUTHORIZATION OF MATHREAD INC. MATHREAD AND MATpoint ARE REGISTERED TRADEMARKS OF MATHREAD INC., WIXOM, MI. ALL RIGHTS ARE RESERVED

COVERED BY ONE OR MORE OF THE FOLLOWING U.S. PATENTS: 5,730,566 , 5,791,849 , 5,836,731 , 5,997,231 , 6,162,001
ADDITIONAL US & INTERNATIONAL PATENTS PENDING