

Date Issued: 12/1/99

Revision Level: AE

Customer Design Standards

MAThread [®]- RADIUSED DOG (PILOT) POINT

CRITICAL DESIGN INFORMATION

START EVERY DESIGN BY FINDING "Lnom"

IF "Lnom" IS NOT GIVEN ON THE CUSTOMER DRAWING, USE EITHER THE MAXIMUM LENGTH (Mmax) OR MINIMUM FULL THREAD LENGTH (Lf) FROM THE CUSTOMER DRAWING TO CALCULATE IT USING ONE OF THE FOLLOWING EQUATIONS

PREFERRED: Lnom = Mmax-Z4-.01SECONDARY: Lnom = Lf+U+.01

Lnom MUST BE ON EVERY PART DRAWING DO NOT CHANGE ANY DIMENSION GIVEN WITHOUT CONSULTING MATHREAD


INSPECTION INFORMATION:

 Lnom ON ROLLED PART IS MEASURED TO THE POINT ON THE LEAD THREAD WHERE IT FIRST REACHES A HEIGHT OF 'W' (0.2xPITCH) WHEN MEASURED FROM THE ROOT OF THE THREAD. (see sketch above)

MAThread SHALL HAVE A MINIMUM OF 1.5 COMPLETE TURNS OF RADIUSED THREAD.
THREAD MUST BE FULLY FORMED, WITH NO UNDER FILL (FLATS, FISSURES) AT PEAK OF
THREAD. WHEN VIEWED IN THE DESIGNATED INSPECTION POSITION, FOUR COMPLETE
RADIUSED THREAD PROFILES MUST BE VISIBLE.

 APPROPRIATE "GO GAGE MUST COMPLETELY PASS OVER MAThread SECTION OF THREAD WITH MINIMAL DRAG BEFORE PLATING. GAGE MUST HAVE MINOR DIAMETER VERIFIED TO ANSI/ASME B1.2-1983 BEFORE USE.

 "Z3" MUST BE MEASURED TO TANGENT POINT OF 'R', USING MAThread APPROVED RADIUS CHART FROM POINT "W" TO TANGENT.



	Mmax ————————————————————————————————————			
PAGE: 11.0	(SEE NOTE 1) (SEE NOTE 1) (REF) (MINIMUM FULL THREAD) (Lf=Lnom01-U)	FINISHED PART DIMENSIONS Z3, Dx, & U MUST NOT BE USED TO DESIGN THE BLANK!	Dx Dx (SEE NOTE 4)	R(REF)
1.0				THIS DOCUMENT

Date Revised: 3/1/09

Page: 11.01

		THREAD SIZE & PITCH	R MIN.	Dy MAX	W ±.0004	Dx	Z ₃ MIN	Z ₄ MAX	U REF			
		1/4-20	0.02	.154	.0100	.189 .193	.065	.100	.150			
	AD	5/16-18	0.03	.190	.0111	.245 .249	.085	.130	.167			
	COARSE THREAD	3/8-16	0.05	.205	.0125	.301 .305	.115	.180	.188			
		7/16-14	0.07	.220	.0143	.352 .356	.135	.220	.214			
		1/2-13	80.0	.260	.0154	.409 .413	.165	.260	.231			
(REF)		9/16-12	0.10	.275	.0167	.464 .468	.180	.295	.250			
		5/8-11	0.12	.290	.0182	.519 .523	.215	.350	.273			
1		DIMENSIONS ARE IN ENGLISH (inch)										
Dy		1/4-28	0.02	.174	.0071	.204 .208	.093	.150	.108			
		5/16-24	0.03	.217	.0083	.259 .263	.117	.195	.125			
<u> </u>	: THREAD	3/8-24	0.04	.272	.0083	.322 .326	.180	.276	.125			
		7/16-20	0.06	.325	.0100	.375 .379	.197	.295	.150			
		1/2-20	0.07	.365	.0100	.438 .442	.240	.358	.150			
	FINE	9/16-18	0.09	.414	.0111	.494 .498	.275	.404	.167			
		5/8-18	0.10	.474	.0111	.557 .561	.308	.466	.167			
THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN IS THE PROPERTY OF MATHREAD INC. ANY USE, DISCLOSURE OR COPYING IS PROHIBITED EXCEPT WITH THE WRITTEN AUTHORIZATION OF MATHREAD INC. MATHREAD AND MATPOINT ARE REGISTERED TRADMARKS OF MATHREAD INC., WIXOM, MI. ALL RIGHTS ARE RESERVED												

SEE PAGE 1,02 FOR PATENT INFORMATION